



TL05A75

PRODUCT DATA

Information issue: August 2026

Product configuration: TL05A75 | SINGLE COLOUR

TL05A75: Ø75 spotlight - 25W 3180lm - 2700K / 3000K / 4000K - CRI 90 - Black / White



DIMENSIONS: Ø75 x 160 mm

Product code

TL05A75

Technical description

Adjustable spotlight for a compatible three-circuit electrified track. Single-colour LED, selectable in 2700K, 3000K or 4000K, CRI 90. Zoomable beam from 15 to 55 degree. The optical assembly provides adjustable zoom optical assembly. Cold-forged aluminium body with thermoplastic front trim, 350 degree rotation, 90 degree tilt and passive thermal management. The integrated driver is housed within the track adapter enclosure.

Installation

Compatible three-circuit electrified track

Colour	Weight (Kg)
--------	-------------

Black / White	0.87 kg (870 g)
---------------	-----------------

Mounting	
----------	--

Three-circuit track	
---------------------	--

CE	RoHS	IP20	Indoor use
----	------	------	------------


Technical data

lm system:	3180	CRI (minimum):	90
W system:	25.0	Colour temperature [K]:	2700 / 3000 / 4000
lm source:	3790	MacAdam Step:	3
W source:	22.0	Life time LED:	> 50,000h - L90 - B10 (Ta 25 C)
Luminous efficacy [lm/W]:	127 (110-145)	Lamp code:	LED
Emergency luminous flux:	0	Lamps / optical assembly:	1
Flux at 90 degree [lm]:	0	ZVEI Code:	LED
L.O.R. [%]:	84	Optical assemblies:	1
Beam angle:	15-55 degree zoomable	Control:	Single colour, non-dimmable

Polar

Lux (55 degree model)

Zoom beam range: 15-55 degree (25W / 3180 lm preliminary model)



h	d	Em	E _{max}
2	2.1	493	815
4	4.2	123	204
6	6.2	55	91
8	8.3	31	51

15-55 degree preliminary model with residual spill at 3180 lm. Not an IES test.